



PRODUCT DETAILS

Product name **Pro-BW® Resin Pigment**

Product type Coloured pigment for **Pro-BW® Plus Resin**

PRODUCT DESCRIPTION

Pro-BW® Resin Pigment is used for achieving the required colour for the **Pro-BW® Plus Resin**, one of **Pro-BW® Plus** system components.

APPLICATION

Pro-BW® Plus system is appropriate for the following substrates:

- Concrete
- Screeds
- Timber
- Asphalt
- Bituminous felt
- Single ply

Pro-BW® Plus system is suitable for use on the following areas:

- Walkways and balconies
- Protected built-up roof
- Inverted built-up roof
- Warm built-up roof
- Warm deck
- Cold deck

Note: Some surfaces may require priming or sacrificial layers.

A wet electronic leak test is required for all inverted/buried systems prior to the waterproofing membrane being covered.

INSTALLATION

Please see the **Pro-BW® Plus Application Guide** for installation instructions.

CERTIFICATION

| Type | Name | Reference |
|------|--------------|-----------|
| BBA | Pro-BW® Plus | 18/5574 |

TECHNICAL INFORMATION

| Characteristic | Value | Unit |
|---------------------|------------|------|
| Physical state | liquid | - |
| Flash point | >93 | °C |
| Viscosity | viscous | - |
| Solubility in water | immiscible | - |

SIZE, FINISH AND COLOUR

| Product Code | Weight kg | Colour |
|---|--------------|---------------|
| BWPPR01SL | 0.6 | Slate Grey |
| BWPPR01CO | 0.6 | Concrete Grey |
| BWPPR01DE | 0.6 | Desert Sand |
| BWPPR01JE | 0.6 | Jet Black |
| BWPPR01OY | 0.6 | Oyster White |
| BWPPR01PA | 0.6 | Pale Green |
| BWPPR01PS | 0.6 | Pastel Sand |
| BWPPR01PV | 0.6 | Pastel Violet |
| BWPPR01PU | 0.6 | Pure White |
| BWPPR01VE | 0.6 | Verdi Green |
| Products are available in all RAL colours dependant on lead times and quantities required Please contact Proteus Waterproofing for further information | | |

SHELF LIFE AND HANDLING

- Shelf life is **12 months** after point of manufacture. Check container for use by date
- Store in a cool, dry, well-ventilated area away from ignition sources and direct sunlight
- Protect from frost

MATERIAL

Non-plasticising pigment (non-hazardous).

PACKAGING

Supplied in **0.6 kg** tins.

LIMITATIONS OF USE

For professional use only.

GUARANTEES

Defects arising from lack of maintenance or abnormal use may fall outside of the cover of the Proteus Waterproofing guarantee.

GUIDELINES AND STANDARDS

It is the responsibility of the Contractor to thoroughly familiarise themselves with all relevant Codes of Practice and Building Regulations to the works or referred in the specification.

Proteus Waterproofing take no responsibility for misinterpretation or lack of knowledge for third parties.

The works shall be carried out in accordance with the requirements of:

- **BS 6229** Flat roofs with continuously supported flexible waterproof coverings - Code of practice
- **BS 8217** Reinforced bitumen membranes for roofing - Code of practice
- **BS 8000-0** Workmanship on construction sites - Introduction and general principles
- **BS 8000-4** Workmanship on building sites - Code of practice for waterproofing
- **LRWA** [Design Guide for Specifiers](#)
- **S2T** [Safe to Torch](#)
- **GRO** [Code of Best Practice](#)