



## PRODUCT DETAILS

Product name	Pro-BW® Resin Pigment
Product type	Coloured pigment for Pro-BW® Plus Resin

## PRODUCT DESCRIPTION

**Pro-BW® Resin Pigment** is used for achieving the required colour for the **Pro-BW® Plus Resin**, one of **Pro-BW® Plus** system components.

## APPLICATION

**Pro-BW® Plus** system is appropriate for the following substrates:

- Concrete
- Screeds
- Timber
- Asphalt
- Bituminous felt
- Single ply

**Pro-BW® Plus** system is suitable for use on the following areas:

- Walkways and balconies
- Protected built-up roof
- Inverted built-up roof
- Warm built-up roof
- Warm deck
- Cold deck

**Note:** Some surfaces may require priming or sacrificial layers.

In all buried/inverted systems prior to the waterproofing membrane being covered, an electronic leak detection test should be carried out by an independent **Roofing and Waterproofing Test Association (RAWTA)** accredited specialist

## INSTALLATION

Please see the **Pro-BW® Plus Application Guide** for installation instructions.

## CERTIFICATION

Type	Name	Reference
BBA	Pro-BW® Plus	22/6183

## TECHNICAL INFORMATION

Characteristic	Value	Unit
Physical state	liquid	-
Flash point	>93	°C
Viscosity	viscous	-
Solubility in water	immiscible	-

## SIZE, FINISH AND COLOUR

Product Code	Weight kg	Colour
BWPPR01SL	0.6	Slate Grey
BWPPR01CO	0.6	Concrete Grey
BWPPR01DE	0.6	Desert Sand
BWPPR01JE	0.6	Jet Black
BWPPR01OY	0.6	Oyster White
BWPPR01PA	0.6	Pale Green
BWPPR01PS	0.6	Pastel Sand
BWPPR01PV	0.6	Pastel Violet
BWPPR01PU	0.6	Pure White
BWPPR01VE	0.6	Verdi Green

Products are available in all RAL colours dependant on lead times and quantities required  
Please contact Proteus Waterproofing for further information

## SHELF LIFE AND HANDLING

- Shelf life is **12 months** after point of manufacture. Check container for use by date
- Store in a cool, dry, well-ventilated area away from ignition sources and direct sunlight
- Protect from frost

## MATERIAL

Non-plasticising pigment (non-hazardous).

## PACKAGING

Supplied in **0.6 kg** tins.

## LIMITATIONS OF USE

For professional use only.

## GUARANTEES

Defects arising from lack of maintenance or abnormal use may fall outside of the cover of the Proteus Waterproofing guarantee.

## GUIDELINES AND STANDARDS

It is the responsibility of the Contractor to thoroughly familiarise themselves with all relevant Codes of Practice and Building Regulations to the works or referred in the specification.

Proteus Waterproofing take no responsibility for misinterpretation or lack of knowledge for third parties.

The works shall be carried out in accordance with the requirements of:

- **BS 6229** Flat roofs with continuously supported flexible waterproof coverings - Code of practice
- **BS 8217** Reinforced bitumen membranes for roofing - Code of practice
- **BS 8000-0** Workmanship on construction sites - Introduction and general principles
- **BS 8000-4** Workmanship on building sites - Code of practice for waterproofing
- **LRWA** [Design Guide for Specifiers](#)
- **S2T** [Safe to Torch](#)
- **GRO** [Code of Best Practice](#)