



PRODUCT DETAILS

Product name **Pro-BW® Sealer Pigment**

Product type Coloured pigment for **Pro-BW® Plus Sealer**

PRODUCT DESCRIPTION

Pro-BW® Sealer Pigment is used for achieving the required colour for the **Pro-BW® Plus Sealer**, one of **Pro-BW® Plus** system components.

APPLICATION

Pro-BW® Plus system is appropriate for the following substrates:

- Concrete
- Screeds
- Timber
- Asphalt
- Bituminous felt
- Single ply

Pro-BW® Plus system is suitable for use on the following areas:

- Walkways and balconies
- Protected built-up roof
- Inverted built-up roof
- Warm built-up roof
- Warm deck
- Cold deck

Note: Some surfaces may require priming or sacrificial layers.

A wet electronic leak test is required for all inverted/buried systems prior to the waterproofing membrane being covered.

INSTALLATION

Please see the **Pro-BW® Plus Application Guide** for installation instructions.

CERTIFICATION

Type	Name	Reference
BBA	Pro-BW® Plus	18/5574

TECHNICAL INFORMATION

Characteristic	Value	Unit
Initial boiling point and boiling range	232	°C
Flash point	107	°C
Relative density <small>water = 1</small>	2.15	-
Viscosity	20000	cSt

SIZE, FINISH AND COLOUR

Product Code	Weight kg	Colour
BWPPS02AN	1.5	Anthracite Grey
BWPPS02BL	1.5	Traffic Black
BWPPS02CO	1.5	Concrete grey
BWPPS02EM	1.5	Emerald Green
BWPPS02GR	1.5	Grass Green
BWPPS02LE	1.5	Leaf Green
BWPPS02LG	1.5	Light Grey
BWPPS02PS	1.5	Pastel Sand
BWPPS02PV	1.5	Pastel Violet
BWPPS02PI	1.5	Pine Green

Products are available in all RAL colours dependant on lead times and quantities required
Please contact Proteus Waterproofing for further information

SHELF LIFE AND HANDLING

- Shelf life is **12 months** after point of manufacture. Check container for use by date
- Store in a well-ventilated are
- Always use relevant safe manual handling techniques relevant to a products size and weight.

MATERIAL

Methacrylate.

PACKAGING

Supplied in metal tins.

LIMITATIONS OF USE

For professional use only.

GUARANTEES

Defects arising from lack of maintenance or abnormal use may fall outside of the cover of the Proteus Waterproofing guarantee.

GUIDELINES AND STANDARDS

It is the responsibility of the Contractor to thoroughly familiarise themselves with all relevant Codes of Practice and Building Regulations to the works or referred in the specification.

Proteus Waterproofing take no responsibility for misinterpretation or lack of knowledge for third parties.

The works shall be carried out in accordance with the requirements of:

- **BS 6229** Flat roofs with continuously supported flexible waterproof coverings - Code of practice
- **BS 8217** Reinforced bitumen membranes for roofing - Code of practice
- **BS 8000-0** Workmanship on construction sites - Introduction and general principles
- **BS 8000-4** Workmanship on building sites - Code of practice for waterproofing
- **LRWA** [Design Guide for Specifiers](#)
- **S2T** [Safe to Torch](#)
- **GRO** [Code of Best Practice](#)