# **GRP Roof Trims**






# **Key features**

- → Neat unobtrusive appearance
- → Simple to handle, work and install
- → Negligible coefficient of expansion, eliminating the problem of membranes tearing at the trim joint
- → Can withstand hot bitumen and mastic asphalt
- → Corrosion resistant
- → Higher strength to weight ratio than its metal counterparts
- → Maintenance free
- → Pre-formed 90° internal and external angles available
- → Choice of 17 profiles in black, white and grey (DE50, L100/100, L40/40 and Flat bar black only)
- → Further colours available to special order
- → Competitively priced
- → Complementary range of fixings, sealant and drill-bits available

### Profiles Flat arm profiles for built-up felt roofing systems (F)






# **Key features**


- → Neat unobtrusive appearance
- → Simple to handle, work and install
- Mill finish ex-stock and available anodised or polyester powder coated to order
- → High strength to weight ratio
- → Maintenance free
- → Pre-formed 90° internal and external angles available
- → Available in a choice of 13 profiles
- → Competitively priced
- → Complementary range of fixings, sealant and drill-bits available

## **Profiles**

# For built-up felt roofing systems



### For mastic asphalt roof finishes



# **Key features**

- → Economical alternative to traditional lead flashing, avoiding the need to cut chases
- → Suitable for built-up felt and mastic asphalt
- → Choice of GRP or aluminium
- → Fix through or cover flashing type available
- → Neat unobtrusive appearance
- → Simple to handle, work and install
- → Complementary range of fixings, sealant and drill-bits available

## **Profiles**

#### **GRP Em-Bars**

